

# E

## H-GB series

### 応用自在のシンプルなデザイン

### 高輝度対応のAll-In-One 汎用 Digital Signage

明るくない、適当なサイズがない、ネットワーク?据え付けは?  
 などの要望にお応えしました。  
 今まで設置できなかった場所でも自在な構成を可能にしました



AMORIS  
 Banquet Reservation via  
 Uptown Call space



高輝度対応モデルで窓際やショーウィンドでも圧倒的なプレゼンスを実現  
 シンプルなデザインで壁掛け、スタンド、天井吊りなどにご利用できます



天井吊り



壁掛け



スタンド:オプション

#### 特徴

- ・プレーヤー内蔵の高輝度オールインワンモデル

#### オプション

- ・高輝度液晶 (1,500cd / 2,000cd / 3,000cd)
- ・タッチパネル、人感センサー
- ・カスタムスタンド (ケース、金具、クーリングシステム)

#### パネルサイズ

17"/19"/24"/32"/40"/42"/46"/47"/52"/55"/65"/70"/82"

#### 取り付け金具オプション

- ・壁掛け用
- ・天井吊り用

### Specifications

#### 高輝度モデル

Model	EH-GB-32SD-NW1500	EH-GB-42LC-NW1500	EH-GB-42LC-NW2000	EH-GB-46SD-NW1500	EH-GB-46LD-NW3000	
Panel	panel type	LCD DID panel	LCD DID panel	LCD DID panel	LCD DID panel	
	diagonal size	32"	42"	42"	46"	
	active display area	697.6845 * 392.256	523.260x930.240	523.260x930.240	572.544x1018.353	572.544x1018.353
	resolution	1366x768	1080x1920	1080x1920	1080x1920	1080x1920
	pixel pitch (VxH)	0.51075 * 0.51075	0.4845x0.4845	0.4845x0.4845	0.7455x0.7455	0.7455x0.7455
	aspect ratio	16:9	16:9	16:9	16:9	16:9
	display colors	8bit-16.7M	8 bit - 16.7M	8 bit - 16.7M	8 bit - 16.7M	8 bit - 16.7M
	brightness	1500cd/m <sup>2</sup>	1500cd/m <sup>2</sup>	2000cd/m <sup>2</sup>	1500cd/m <sup>2</sup>	3000cd/m <sup>2</sup>
	contrast ratio	4000:1	1400:1	1400:1	2000:1	2000:1
	response time (G/G)	8ms	5ms	5ms	8ms	8ms
viewing angle (H/V)	178° / 178°	178° / 178°	178° / 178°	178° / 178°	178° / 178°	
life time	50,000hrs average	50,000hrs average	50,000hrs average	50,000hrs average	50,000hrs average	
Power Supply		AC100~240V	AC100~240V	AC100~240V	AC100~240V	
Connectivity	signal input	D-Sub, DVI	D-Sub, DVI	D-Sub, DVI	D-Sub, DVI	
	storage	CF card, USB	CF card, USB	CF card, USB	CF card, USB	
Dimension	width (mm)	763	980	980	1100	
	height (mm)	453	553	553	653	
	depth (mm)	80	96	96	98	98
Weight (kg)		28	40	40	55	55
Supporting file format		WMA, WAV, MP3, JPEG, MPEG2, MPEG4, AVI, Xvid, DivX, H263, WMV9				
Network		LAN : 10/100Mbps, Wireless LAN : 802.11b/g				
OSD language		English				
Player board		Built-in set-top box				
Accessories		Remocon, Built-in speakers, Power cord				
Operating Temperature		-20 C ~50 C				

#### — 高輝度モデル —

Model	EH-GB-52SD-NW2000	EH-GB-52SD-NW700	EH-GB-70SD-NW600	EH-GB-82SD-NW600	
Panel	panel type	LCD DID panel	LCD DID panel	LCD DID panel	LCD DID panel
	diagonal size	52"	52"	70"	82"
	active display area	648x1152	648x1152	871.56x1549.44	1015.74x1805.76
	resolution	1080x1920	1080x1920	1080x1920	1080x1920
	pixel pitch (VxH)	0.6x0.6	0.6x0.6	0.807x0.807	0.9405x0.9405
	aspect ratio	16:9	16:9	16:9	16:9
	display colors	8 bit - 16.7M	8 bit - 16.7M	8 bit - 16.7M	8 bit - 16.7M
	brightness	2000cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>
	contrast ratio	1700:1	1700:1	1500:1	1200:1
	response time (G/G)	8ms	8ms	8ms	8ms
viewing angle (H/V)	178° / 178°	178° / 178°	178° / 178°	178° / 178°	
life time	50,000hrs average	50,000hrs average	50,000hrs average	50,000hrs average	
Power Supply		AC100~240V	AC100~240V	AC100~240V	AC100~240V
Panel	signal input	D-Sub, DVI	D-Sub, DVI	D-Sub, DVI	D-Sub, DVI
	storage	CF card, USB	CF card, USB	CF card, USB	CF card, USB
Panel	width (mm)	1202	1202	1640	1898
	height (mm)	690	690	486	1103
	depth (mm)	102	102	130	180
Weight (kg)		65	65	100	120
Supporting file format		WMA, WAV, MP3, JPEG, MPEG2, MPEG4, AVI, Xvid, DivX, H263, WMV9			
Network		LAN : 10/100Mbps, Wireless LAN : 802.11b/g			
OSD language		English			
Player board		Built-in set-top box			
Accessories		Remocon, Built-in speakers, Power cord			
Operating Temperature		-20 C ~50 C			



お問い合わせ

Specal Solution Pertoner  
アイティ・ニュース株式会社  
<http://www.itnews.co.jp/>